



mEssfix

NEDO
GmbH & Co. KG
Hochgerichtstraße 39-43
D-72280 Dornstetten

Tel.: +49 7443 2401 0
Fax: +49 7443 2401 45
www.nedo.com
info@nedo.com

OPERATING INSTRUCTIONS

The **NEDO** “mEssfix” telescopic measuring rod is a high quality product. To ensure its functional reliability and service life, we recommend you to observe the following points:

1. Handle the telescopic measuring rod with all the care usual for measuring instruments.
2. Do not push together the telescopic elements when they are dirty; carefully clean them first.
3. The rod is not suitable for measuring the depth of liquids. The telescopic elements **must not** be oiled.
4. The **NEDO** telescopic measuring rod will conduct electricity. Take care to keep it out of contact with electrical cables, etc.
5. Regularly check the functional reliability and measurement accuracy of the measuring rod. A simple method of doing this is to compare it against a metre rule. In addition, when the rod is fully retracted the display reading must lie within the following measurement ranges:

3m mEssfix 69,7 – 70,1 cm	3m Roller-shutter mEssfix 79,7 – 80,1 cm
4m mEssfix 86,3 – 86,7 cm	4m Roller-shutter mEssfix 96,3 – 96,7 cm
5m mEssfix 107,2 – 107,6 cm	5m Roller-shutter mEssfix 117,2 – 117,6 cm

6. Use the protective bag for transporting and storing the rod.