



On Level 6020 Surface Mounted Kit For 21.5mm - Anod Alum (Model: K.ON.10.6020.SUKIT.021)



• Only 60mm wide this profile can achieve a line load level of 1.5kN with the appropriate glass selection.


• Extremely fast and easy installation. Can be fully installed from the balcony side avoiding the need for scaffolding or hoists

• Finished in a Anodised Aluminium look as standard with other colours and finishes available on request.

• Kit contains 2.5 metres of the main surface mounted profile and the glass clamps and gaskets suitable for a 2.5 metre installation.

• Endcaps, corners, joining pins, etc. sold separately.

• Non-stock item. Shipped direct from Manufacturer. Delivery usually 3-7 days.



Attributes:

Product Code: K.ON.10.6020.SUKIT.021

Unit Of Sale: 2.5 Mtr

| | |
|--|--|
| | <p>MODEL 6020</p> <p>MOUNTING 1.0 kN Top mount</p> <p>APPLICATION Private, commercial and public areas</p> <p>GLASS THICKNESS 12 - 21.52 mm</p> <p>COLOR LINE ✓</p> <p>WATER DRAINAGE ✓</p> <p>COVER STRIP ✗</p> <p>AVAILABLE IN 3.0 kN ✗</p> <p>MOUNTING DISTANCE 400 mm 1.5 kN 600 mm 0.74 kN</p> |
|--|--|

